



**UNIVERSITI PUTRA MALAYSIA**

**WATER BALANCE STUDY OF TONLE BATI IRRIGATION  
PROJECT, CAMBODIA**

**LENG CHREANG**

**FK 1999 1**

**WATER BALANCE STUDY OF TONLE BATI IRRIGATION  
PROJECT, CAMBODIA**

**By  
LENG CHREANG**

**Thesis Submitted in Fulfilment of the Requirements for the  
Degree of Master of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**October 1999**



## **ACKNOWLEDGEMENTS**

I would like to express my sincerest gratitude to my supervisor, Dr. Abdul Aziz Zakaria, for his untiring guidance, advice, support and encouragement throughout my study program. I am very much grateful to the members of my supervisory committee, Assoc. Prof. Kwok Chee Yan and Assoc. Prof. Dr. Mohd Amin Mohd Soom, for their valuable suggestions and opinions that led to the refinement of the manuscript

I am very grateful to Southeast Asian Research Council for Agriculture (SEARCA) based in the College, Los Banos, Philippines for the scholarship grant and to the German Academic Exchange Service (DAAD) for providing the fund through SEARCA that enabled me to study in Malaysia and complete my thesis.

I am thankful to the Ministry of Agriculture, Forestry and Fisheries of Cambodia for its support and in maintaining my job post during my study in Malaysia. My sincere thanks goes to the Director of Bati Agricultural Development Center and his staff, especially Mr. Le Pat, for their information, discussion and suggestions, and help during my fieldwork.

I would like to extend my heartfelt thanks to my parents, Mr. and Mrs. Leng Nam, and to my wife and son for their love, understanding and encouragement to complete this study.

Finally, I am thankful to God for making all things possible.

## TABLE OF CONTENTS

	<b>Page</b>
<b>ACKNOWLEDGEMENTS</b>	11
<b>LIST OF TABLES</b>	v
<b>LIST OF FIGURES</b>	vii
<b>LIST OF PLATES</b>	ix
<b>ABSTRACT</b>	x
<b>ABSTRAK</b>	xii
 <b>CHAPTER</b>	
 <b>I INTRODUCTION</b>	 1
General Situation	1
Rice Production and Cropping Systems	2
Background of the Study	4
Statement of the Problem	5
Objective of the Study	7
 <b>II LITERATURE REVIEW</b>	 8
Crop Evapotranspiration	8
Water Balance	12
Percolation	16
Rainfall and Effective Rainfall	19
Irrigation Water Requirement	23
Drainage	26
Water Use Efficiency	27
 <b>III MATERIALS AND METHODOLOGY</b>	 30
Experimental Site	30
Materials	33
Experimental Duration	33
Methodologies	33
Experimental Layout	33
Field Water Control	35
Water Balance	35
Measurement Methods	36
Evapotranspiration and Percolation	36
Pan Evaporation	39
Rainfall and Effective Rainfall	39
Irrigation and Drainage	40

<b>IV RESULTS AND DISCUSSION .....</b>	<b>44</b>
Actual and Reference Crop Evapotranspiration .....	45
Deep Percolation and Lateral Seepage .....	54
Pan Evaporation .....	58
Rainfall and Effective Rainfall .....	61
Irrigation and Drainage .....	63
Water Use Efficiency .....	67
<b>V CONCLUSION AND RECOMMENDATION .....</b>	<b>69</b>
<b>BIBLIOGRAPHY .....</b>	<b>72</b>
<b>APPENDIX</b>	
<b>A: Experimental Results.....</b>	<b>75</b>
<b>B: Formula and Format for Calculation of Penman Method...</b>	<b>93</b>
<b>VITA .....</b>	<b>103</b>

## LIST OF TABLES

Table	Page
1 Present and Future Land Use in Tonle Bati Area .....	31
2 Comparison between the Study Result with Previous Study Results .....	52
3 Evapotranspiration Ratio to Pan Evaporation .....	60
4 Pan Coefficient .....	60
5 Water Requirements for Phcar Khney, Kung Sor and IR66 ...	66
6 Water Use Efficiency .....	
7 Daily Water Balance Sheet (Plot 1) ...	
8 Daily Water Balance Sheet (Plot 2) ...	
9 Daily Water Balance Sheet (Plot 3) ...	
10 Daily Pan Evaporation and Temperature Water in Evaporation Pan .....	86
11 Daily Rainfall for Wet Season 1998 .....	87
12 10-day Interval Values of Water Balance Components (Variety: Phcar Khney, Plot 1) .....	88
13 10-day Interval Values of Water Balance Components (Variety: Kung Sor, Plot 2) .....	89
14 10-day Interval Values of Water Balance Components (Variety: IR 66, Plot 3) .....	
15 $K_c$ Values by 10-day Interval for Rice .....	
16 Seasonal Total of Water Balance Components .....	92
17 Saturation Vapour Pressure over Water in millibars .....	97

18	Extra Terrestrial Radiation ( $R_a$ ) Expressed in Equivalent Evaporation in mm/day .....	98
19	Mean Daily of Maximum Possible Sunshine Hours (N) for Different Month and Altitude .....	99
20	Effect of Temperature $f(T)$ on Longwave Radiation ( $R_{nl}$ ) .....	99
21	Values of Weighting Factor (1-W) for the Effect of Wind and Humidity on $ET_o$ at Different Temperature and Altitude .....	100
22	Values of Weighting Factor (W) for the Effect of Radiation on $ET_o$ at Different Temperature and Altitude .....	100
23	Adjustment Factor [c] in Presented Penman Equation .....	101
24	Daily Reference Crop Evapotranspiration for Wet Season 1998....	102

## LIST OF FIGURES

Figure	Page
1 Components of Soil Water Balance .....	14
2 Container Technique for Determining $ET_c$ and Effective Rainfall for Rice .....	21
3 Map of Cambodia Showing the Study Area .....	
4 Experimental Layout for Determining Water Balance Components of the Paddy Field .....	
5 Components of Water Balance for Paddy Field .....	
6 A Pair of Micro-lysimeters with and without Bottom .....	37
7 Daily Reference Crop and Actual Evapotranspiration for Phcar Khney, Kung Sor, and IR 66 (from August 20, 1998).....	46
8 Daily Average of Humidity and Mean Temperature for Phnom Penh ...	47
9 Daily Maximum Wind Speed and Sunshine Hours for Phnom Penh ...	47
10 Reference Crop and Actual Evapotranspiration Values (10-day Interval) for Three Rice Varieties ...	
11 Crop Coefficient ( $K_c$ ) for Rice .....	50
12 Relationship between Cumulative Evapotranspiration and Growth Stages for Rice Crop .....	
13 Deep Percolation and Lateral Seepage Values (10-day Interval) for Three Plots .....	56
14 Cumulative Deep Percolation and Lateral Seepage Values (10-day Interval) for Three Plots .....	57
15 10-day Interval Values of Pan Evaporation for Phnom Penh and Experimental Site .....	58



16	Ratio of Evapotranspiration to Pan Evaporation for Three Rice Varieties	58
17	Rainfall and Effective Rainfall at 10-day Interval for Three Plots	62
18	Rainfall from Phnom Penh and Experimental Site at 10-day Interval	63
19	Irrigation, Rainfall and Drainage Water at 10-day Interval for Three Plots	65
20	Seasonal Total Evapotranspiration, Percolation and Seepage (Top), and Irrigation, Rainfall and Drainage (Bottom)	68

## LIST OF PLATES

Plate		Page
1	Evaporation Pan (U.S class A Standard) .....	41
2	Rain Gauge (Copper Model) .....	41
3	Experimental Layout View .....	42
4	Transplanting in Experimental Plots .....	42
5	Experimental Plots View .....	43
6	Micro-lysimeters View .....	43



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in  
fulfilment of the requirements for the degree of Master of Science.

**WATER BALANCE STUDY OF TONLE BATI IRRIGATION  
PROJECT, CAMBODIA**

By

**LENG CHREANG**

**October 1999**

**Chairman : Dr. Abdul Aziz Zakaria**

**Faculty : Engineering**

This study on water balance in the paddy field was done to determine crop evapotranspiration and water use efficiency. The experiment was conducted during the main season for three rice varieties, namely: Phcar Khney, Kung Sor and IR66. All varieties were nursed and transplanted in three adjacent plots. Three plots, 100 square meters each, were prepared in a large paddy field. The transplanting spacing in the experimental plots was 20×20 cm and the number of seedlings per hill was 3. The results obtained on seasonal water requirement for evapotranspiration varied with varieties. They were 680, 771 and 454 mm for Phcar Khney, Kung Sor, and

IR66, respectively. Daily average evapotranspiration was 6.1 mm/day throughout the season for all varieties.

Water use efficiency was calculated by using equation  $(ET_c + S\&P)/(IR + RF)$ . The results obtained ranged from 50% to 71%, or an average of 63% for the three plots. For an area, where lateral seepage is negligible, the water use efficiency should be 60% for wet season rice.

The cumulative seepage and percolation were –59, 156 and 232 mm for 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> plot, respectively. Daily average percolation was about 1mm/day throughout the wet season. Water depth of 368 to 484 mm was recorded as supplementary irrigation water requirement at the early part of the season. Drainage water ranged from 282 to 753 mm based on the difference in duration of rice growing periods.

In addition, pan evaporation and effective rainfall were also recorded and calculated. Daily average evaporation was 4.15 mm/day, and for the effective rainfall it was about 55% throughout the wet season.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi syarat keperluan untuk ijazah Master Sains.

**KAJIAN KESEIMBANGAN AIR UNTUK PROJEK  
PENGAIARAN TONLE BATI, CAMBODIA**

Oleh

**LENG CHREANG**

**October 1999**

**Pengerusi : Dr. Abdul Aziz Zakaria**

**Fakulti : Kejuruteraan**

Kajian mengenai keseimbangan air di sawah padi dilakukan bertujuan untuk menentukan evapotranspirasi dan kecekapan penggunaan air pada tanaman. Eksperimen dilakukan pada musim utama penanaman tiga jenis variati padi, iaitu Phcar khney, Kung Sor dan IR66. Semua variati disemai di tapak semaian dan kemudian dipindahkan ke tiga petak bersebelahan. Setiap petak adalah seluas 100 meter persegi. Ketiga-tiga petak ini disediakan dalam sawah padi yang luas. Anak-anak padi ditanam pada jarak 20×20 cm dalam petak eksperimen dan 3 anak padi ditanam pada setiap lubang tanaman. Keputusan bagi keperluan air semusim untuk evapotranspirasi adalah berbeza mengikut variati, iaitu 680 mm bagi Phcar Khney,

771 mm bagi Kung Sor dan 454 mm bagi IR66. Purata evapotransprasi harian adalah 6.1 mm/hari sepanjang musim itu bagi kesemua variasi.

Kecekapan penggunaan air dikira dengan menggunakan persamaan  $(ET_c + S \& P) / (IR + RF)$ . Keputusan adalah dalam lingkungan 50% ke 70% atau purata sebanyak 63% untuk ketiga-tiga petak. Untuk sesuatu kawasan dengan susupan sisi boleh diabaikan, kecekapan air ialah 60% bagi padi pada musim itu.

Susupan timbunan dan resapan adalah -59, 156 dan 232 mm bagi petak pertama, kedua dan ketiga. Purata resapan harian adalah kira-kira 1mm/hari sepanjang musim tersebut. Kedalaman air yang direkod adalah dalam lingkungan 368 ke 484 mm dengan air tambahan dari julat 282 ke 753 mm berasaskan perbezaan hayat pada tempoh pertumbuhan padi.

Sebagai tambahan, evaporasi pan dan hujan berkesan juga direkod dan dianalisiskan. Purata harian penyejatan adalah 4.15 mm/hari dan hujan berkesan adalah sebanyak 55% sepanjang musim tersebut.

# **CHAPTER I**

## **INTRODUCTION**

### **General Situation**

The Kingdom of Cambodia is located in the Indochina Peninsular with a total area of 181,035 square kilometres. Its population was estimated at about 10.2 million in 1995, with yearly average growth rate of 2.5% to 2.8%. Cambodia is an agricultural country. About 80% of the Cambodian population lives in rural areas and dependent on agriculture particularly rice cultivation, for their livelihood.

Rice is the dominant crop followed by rubber. Most of the cultivated areas are devoted to rice. Rice consumption (milled rice) was estimated at 151.2 kg per person per year (MAFF, 1996-97). Important cash crops are legumes, maize, vegetable, tobacco, sesame, cassava, sugar cane, jute and potatoes.

Cambodia's climate is dominated by the tropical monsoon that provide two different seasons in a year (Wet and Dry season). Wet season (rainy season) starts from April/May and ends in October/November, while Dry season (dry but cool) starts from November/December and recedes in April/May. The average annual rainfall for most irrigated areas is about 1,200mm to 1,600mm. The average annual temperature ranges from 25 °C to 29 °C, while the mean daily temperature varies from 19 °C in January to 35 °C in April.

The water source of Cambodia is mainly supplied by the Mekong/Tonle Sap/Bassac system. Bassac River is a branch of the Mekong River, while Great Lake-Tonle Sap is a Mekong tributary. The mean annual run-off at Phnom Penh is  $413 \times 10^9 \text{ m}^3$ . When the discharge of the Mekong at Phnom Penh rises above  $15,000 \text{ m}^3/\text{sec}$ , its flow not only runs to the Great Lake, but also overflows into channels toward the low-lying areas along the Bassac and Mekong. The annual flooding of the Delta and Great Lake-Tonle Sap areas determines to a large extent the agroecological constraints and opportunities. Flooding limits crop production for deeply inundated areas, except for deep water floating rice.

### **Rice Production and Cropping System**

Farmland occupy about 3,800,000 ha or 21% of the total areas, to which 2,700,000 ha are paddy fields. The cultivated areas are mainly located in the lowland around the Tonle Sap Lake and on both sides of the Mekong River in the south of the country. Rice production was estimated at about 3.4 million-ton with an average yield of 1.83 tonnes per hectare in 1996. Up to now, rice production is mainly concentrated during the wet season. However, there are three distinct rice-cropping systems in Cambodia:

1. Wet season cropping
2. Dry season cropping, and
3. Recession cropping.



For wet season, rice is cultivated under rain-fed condition, with supplementary irrigation using water stored in reservoirs or direct abstraction from rivers by gravity and pumping. The potential yield increase due to the supplementary irrigation is considered small (0.5MT/ha) and usually insufficient to justify the provision of irrigation infrastructure (Halcrow, 1995).

During dry season, rice is grown in part of the area where water is available through irrigation system. Usually, only a small part of the rice areas can be irrigated during dry season, because of water shortage. During dry season, rice cultivation without irrigation is impossible. With irrigation, the risk of drought is reduced and, farmers are encouraged to invest in higher yielding varieties, fertilizers and insecticides. Rice yields under irrigation are higher than under the rain-fed condition.

Recession rice is cultivated during the dry season, on the land that is heavily flooded in the wet season. The cultivated areas are close to the Tonle Sap, Bassac, and Mekong system, and rely on natural flooding to water the field before land preparation. The crop is transplanted and irrigation through the growing season is made by using water held in reservoirs or pumped from the main rivers. The yield under this cropping system, indeed, is higher because the low-lying alluvial associated with recession cropping is usually more fertile. Recession rice in reservoir area itself is also carried out in some other locations.

### **Background of the Study**

To improve food security through expansion in the production of rice and other food crops is the basic goal of the Royal Government of Cambodia in the agricultural sector. The Strategic Plans of the Ministry of Agriculture, Forestry and Fisheries of Cambodia in increasing the production of rice are (1) to increase cultivated areas (land reclamation and double cropping), and (2) to raise the yield per unit area.

Increasing the yield per unit of area can be achieved in many ways, but one of the most important in Cambodia is improvement of water control and management. Water control and management in Cambodia involve the following:

1. controlling flood and excess water
2. ensuring adequate water supply
3. making efficient use of a limited supply of water

Water availability is a major constraint at present. This is due either to a limited source or the inability of the infrastructure to abstract, store or convey the required amount of water. In many cases, both constraints occur together (Halcrow, 1994). The farmers are suffering from shortage of irrigation water for cultivating rice even in the wet season, particularly in the beginning of the wet season.

In Cambodia there are many areas suitable for double cropping, if water could be made available. In this case, improving Irrigation facilities (designing, rehabilitation and construction) and efficient ways of using limited amount of water available are crucial factors that will determine the success of the Government's goal of increasing food production.

Water balance study in the paddy field can provide the most important data for improving on-farm water management. Crop water requirement varies within different crops, cultivated area, cropping system and others.

This study hopes to provide some data on crop evapotranspiration, pan evaporation, seepage and percolation, irrigation and drainage requirement, rainfall and effective rainfall, and water use efficiency that can be useful to irrigation management for rice crop production in Cambodia.

### **Statement of the Problem**

Rice is the main crop in Cambodia, but rice cultivation mostly depends on rain-fed condition hence results in low yield and unreliable production. Of the total 841 irrigation systems, 176 (21%) are fully operational, 550 (65%) are partially operational, and 115 (14%) are not operational at all (Halcrow, 1994). These irrigation systems have a total existing area of 172,727 ha in the wet season and 103,656 ha in the dry season. These figures excluded systems with an existing or potential area of less than 10 ha.

In 1992, irrigation can only supplement for wet season rice about 173,000 ha (9.4%) and irrigated dry season rice about 104,000 ha (5.7%). Irrigation and drainage systems are presently not functioning well; especially those constructed during the Pol Pot regime (1975-79) because of the poor design. This situation has shown the need for data in designing and management of irrigation and drainage systems.

Six out of the 10 research stations in Cambodia are working on rice experiment and rice seed production and 7 agricultural development centres provide services for water irrigation and farm-input supplies for rice cultivation. However activities of most of these stations and centers have decreased to a limited areas or not active due to the shortage of funds.

In many cultivated areas, data on crop evapotranspiration and related water management data are not available. Master Plan Study and Feasibility Study on Agricultural and Rural Development Project were conducted in Kandal and Takeo provinces. In this study (JICA, 1995), crop evapotranspiration was estimated by using the meteorological data from Phnom Penh, while crop coefficient was estimated with reference to irrigation and drainage paper “Crop Water Requirement” conducted by FAO. On Prek Thnot Multipurpose Project, Reappraisal report (Euroconsult, 1991), crop evapotranspiration was estimated by using climatic data from Phnom Penh too. This also showed the lack of actual evapotranspiration data in the study area.

Pochentong Meteorological Station (Phnom Penh) is the only station that can provide meteorological data (long term record) for computation of crop evapotranspiration. The lack of data on these aspects is the main problem when it comes to the designing and management of irrigation systems and agricultural development projects in Cambodia.

### **Objective of the Study**

The objective of this study is to carry out a water balance study of a paddy field in Tonle Bati Irrigation Project. The specific objectives are:

- 1-To determine evapotranspiration of rice crop during the main season,
- 2-To determine the irrigation requirement of paddy field, and
- 3-To determine water use efficiency of an irrigated paddy plot.

## **CHAPTER II**

### **LITERATURE REVIEW**

#### **Crop Evapotranspiration**

Crop evapotranspiration is one of the important elements of the hydrological cycle process. Crop evapotranspiration is defined as “the depth of water needed to meet the water loss through evapotranspiration of a disease-free crop growing in large field under non-restricting soil conditions, including soil water and fertility and achieving full production potential under the given growing environment” (Doorenbos & Pruitt, 1977).

Crop evapotranspiration is the sum of two processes: (1) evaporation and (2) transpiration. Evaporation is the loss of water in vapour form from the free water surface, while transpiration is the amount of water entering plant's roots and used to build plant tissues and the excess is passed through the leaves of the plant to the atmosphere. Crop evapotranspiration is usually expressed in depth of water per unit of time such as mm/day or mm/month.

Crop evapotranspiration can be measured directly from the field by several methods such as lysimeter, water balance study and soil analysis method. Lysimeter method provides complete information on all components of water balance. But due to the difficulty of obtaining accurate field measurement, prediction method for crop evapotranspiration is used. To predict crop

evapotranspiration, reference crop evapotranspiration and crop coefficient are needed for estimation.

Reference crop evapotranspiration is defined as “the rate of evaporation from an extensive surface of 8 to 15 cm tall, green grass cover of uniform height, actively growing, completely shading the ground and not short of water” (Doorenbos & Pruitt, 1977).

The relation between crop evapotranspiration and reference crop evapotranspiration is given as follows:

$$ET_c = K_c \times ET_o \quad (1)$$

where,  $ET_c$  = Crop evapotranspiration, mm

$ET_o$  = Reference crop evapotranspiration, mm

$K_c$  = Crop coefficient

Reference crop and actual evapotranspiration vary under different climatic condition. Its value increases with increasing temperature, sunshine, wind speed and less of humidity. Doorenbos & Pruitt (1977) recommended four methods for estimating reference crop evapotranspiration, including:

- Blaney-Criddle method
- Radiation method
- Penman method, and
- Pan Evaporation method

Meteorological data, including temperature, radiation, wind velocity, sunshine duration, and humidity are needed in computing reference crop evapotranspiration.

Measurement of evapotranspiration of rice crop, in general, can be achieved by using lysimeter, since it grows with standing water. Lysimeter can be divided into two groups: (1) non-weighing lysimeter and (2) weighing lysimeter.

Weighing lysimeter can measure evapotranspiration in short period (hourly) with high accuracy. Unfortunately it is very expensive. For a good installation, the total cost may be very prohibitive.

For non-weighing lysimeter, however, the accuracy is lower. It is a large container filled with soil, in which crops are grown under natural condition. Water loss or gain can be measured. The container is fitted with suitable inlets for irrigation and outlets for drainage. The lysimeter is buried in the field and the same crop, as grown inside, surrounded it.

Rice lysimeters used to measure evapotranspiration, percolation and effective rainfall are tank lysimeter, drum technique, and micro-lysimeter. In 1971 Sugimoto used tanks, 91×91×61cm, to measure evapotranspiration of rice crop in Telok Chengai Padi Experimental Station and Sala Kanan Padi Test Station in Malaysia. Van De Goor and Zijlstra in 1977 also used two square tanks with bottom, 91×91×91cm, to measure evapotranspiration of rice crop in lowland rice of Malaysia.



Dastane *et al* (1966) used 3 drums for assessing evapotranspiration, percolation, water requirement and ineffective rainfall of rice crop. The drum was 50 cm in diameter and 125 cm in height (Figure 2). It was embedded in paddy field leaving about a quarter of its height above ground level. Dastane (1974) suggested that the drum technique gave promising results. The method requires replications to give accurate data. This is an inexpensive method.

Ramlee (1991) used micro-lysimeter, with PVC tubes of 20cm diameter and 60 cm height, to measure evapotranspiration and percolation in the paddy field of Project Bersepadu Seberang Perak in Malaysia.

However, rice is generally grown with standing water, hence evapotranspiration is never restricted by the lack of soil moisture, and it will always be at the maximum possible under the climatic condition i.e. potential evapotranspiration.

Evapotranspiration, however, is fairly constant throughout the growing period, except for the minor variation due to the influence of cloudiness, humidity, and wind. Shortly after transplanting, evapotranspiration is mainly evaporation, but as the crop develops, the share of transpiration increases and evaporation decreases, until evapotranspiration is mostly transpiration when the crop is vegetatively developed (Van De Goor, 1977).

For lowland rice, daily evapotranspiration rate vary with a narrow range from 6 mm to 8 mm per day during the whole growing season, irrespective of